

IN THE CLAIMS

1. (Previously Amended) A method for detecting an object
of interest in an image processing system, the method comprising
5 the steps of:

generating a difference image;
segmenting the difference image into a plurality of
regions, wherein the difference image is segmented into a
plurality of regions such that each of the regions are bounded
10 by one or more lines passing through the entire image;
identifying one or more silhouette candidates in at
least a subset of the regions; and
detecting the object of interest based at least in
part on the identified silhouettes.

15

2. (Original) The method of claim 1 wherein the object of
interest comprises a moving person.

3. (Original) The method of claim 1 wherein the
20 difference image comprises a thresholded difference image
generated by taking a difference between a first image and a
second image and applying binary thresholding to the resulting
difference.

25 4. (Original) The method of claim 1 wherein the
difference image is segmented into a plurality of regions such
that each of the regions are bounded by one or more vertical
lines passing through the entire image.

5. (Original) The method of claim 1 wherein each of the regions of the image which includes a silhouette candidate includes only a single silhouette candidate.

5 6. (Original) The method of claim 1 further including the step of determining saliency values for each of the silhouette candidates using tensor voting.

7. (Original) The method of claim 2 further including the
10 step of detecting a neck position of the moving person by analyzing a sum of x-components of tangents along a corresponding silhouette.

8. (Original) The method of claim 7 further including the
15 step of utilizing the detected neck position to determine at least one of a head position and a head size for the moving person.

9. (Previously Amended) An apparatus for detecting an
20 object of interest in an image processing system, the apparatus comprising:

a camera; and

a processor coupled to the camera and operative (i) to generate a difference image from a signal received from the
25 camera; (ii) to segment the difference image into a plurality of regions, wherein the difference image is segmented into a plurality of regions such that each of the regions are bounded by one or more lines passing through the entire image; (iii) to identify one or more silhouette candidates in at least a subset

of the regions; and (iv) to detect the object of interest based at least in part on the identified silhouettes.

10. (Original) The apparatus of claim 9 wherein the object
5 of interest comprises a moving person.

11. (Original) The apparatus of claim 9 wherein the
difference image comprises a thresholded difference image
generated by taking a difference between a first image and a
10 second image and applying binary thresholding to the resulting
difference.

12. (Original) The apparatus of claim 9 wherein the
difference image is segmented into a plurality of regions such
15 that each of the regions are bounded by one or more vertical
lines passing through the entire image.

13. (Original) The apparatus of claim 9 wherein each of
the regions of the image which includes a silhouette candidate
20 includes only a single silhouette candidate.

14. (Original) The apparatus of claim 9 wherein the
processor is further operative to determine saliency values for
each of the silhouette candidates using tensor voting.

25

15. (Original) The apparatus of claim 10 wherein the
processor is further operative to detect a neck position of the
moving person by analyzing a sum of x-components of tangents
along a corresponding silhouette.

30

16. (Original) The apparatus of claim 15 wherein the processor is further operative to utilize the detected neck position to determine at least one of a head position and a head size for the moving person.

5

17. (Original) The apparatus of claim 9 wherein the image processing system comprises a video conferencing system.

18. (Original) The apparatus of claim 9 wherein the image
10 processing system comprises a video surveillance system.

19. (Original) The apparatus of claim 9 wherein the image processing system comprises a human-machine interface.

15 20. (Previously Amended) An article of manufacture comprising a storage medium for storing one or more programs for detecting an object of interest in an image processing system, wherein the one or more programs when executed by a processor implement the steps of:

20 generating a difference image;

segmenting the difference image into a plurality of regions, wherein the difference image is segmented into a plurality of regions such that each of the regions are bounded by one or more vertical lines passing through the entire image;

25 identifying one or more silhouette candidates in at least a subset of the regions; and

detecting the object of interest based at least in part on the identified silhouettes.

30